

# 11. ES 11: Use at industrial sites; Use of nickel oxide powder for the production of nickel zinc ferrite cores

## 11.1. Title section

Product category: Metal surface treatment products (PC 14)

Sector of use: Manufacture of computer, electronic and optical products, electrical equipment (SU 16)

<b>Environment</b>	
1: Use of nickel oxide powder for the production of nickel zinc ferrite cores - Discharge to fresh water via municipal sewage treatment plant	ERC 5
2: Use of nickel oxide powder for the production of nickel zinc ferrite cores - Direct discharge to fresh water	ERC 5
3: Use of nickel oxide powder for the production of nickel zinc ferrite cores - Direct discharge to marine water	ERC 5
<b>Worker</b>	
4: Raw material handling	PROC 26
5: Milling	PROC 2
6: Spray drying	PROC 4
7: Calcination	PROC 22
8: Sintering	PROC 22
9: Handling of nickel zinc solids	PROC 21
10: Wet cleaning	PROC 28
11: Cleaning/removal of dust	PROC 28
<b>Subsequent service life exposure scenario(s)</b>	
ES 12: Service life (worker at industrial site); Machinery, mechanical appliances, electrical/electronic articles; Service life of nickel-containing electronics/ferrite cores in industrial settings	
ES 13: Service life (professional worker); Machinery, mechanical appliances, electrical/electronic articles; Service life of nickel-containing electronics/ferrite cores in professional settings	

## 11.2. Conditions of use affecting exposure

### 11.2.1. Control of environmental exposure: Use of nickel oxide powder for the production of nickel zinc ferrite cores - Discharge to fresh water via municipal sewage treatment plant (ERC 5)

<b>Amount used, frequency and duration of use (or from service life)</b>
Daily amount per site <= 1.5 tonnes/day (All the amounts and concentrations are expressed as Ni as this is the driver for the environmental risk assessment.)
Annual amount per site <= 337.5 tonnes/year
Emission days >= 225 days/year
<b>Technical and organisational conditions and measures</b>
Chemical precipitation or sedimentation or filtration or electrolysis or reverse osmosis or ion exchange

Electrostatic precipitator or wet electrostatic precipitator or cyclones or fabric/bag filter or ceramic/metal mesh filter or wet scrubber
<b>Conditions and measures related to biological sewage treatment plant</b>
Municipal sewage treatment plant is assumed.
Assumed domestic sewage treatment plant flow $\geq 2E3$ m <sup>3</sup> /day
<b>Conditions and measures related to external treatment of waste (including article waste)</b>
Dispose of waste product or used containers according to local regulations.
<b>Other conditions affecting environmental exposure</b>
No discharge to marine water assumed
Receiving water dilution (fresh or marine) $\geq 10$
Receiving surface water flow $\geq 1.8E4$ m <sup>3</sup> /day

### 11.2.2. Control of environmental exposure: Use of nickel oxide powder for the production of nickel zinc ferrite cores - Direct discharge to fresh water (ERC 5)

<b>Amount used, frequency and duration of use (or from service life)</b>
Daily amount per site $\leq 1.5$ tonnes/day (All the amounts and concentrations are expressed as Ni as this is the driver for the environmental risk assessment.)
Annual amount per site $\leq 337.5$ tonnes/year
Emission days $\geq 225$ days/year
<b>Technical and organisational conditions and measures</b>
Chemical precipitation or sedimentation or filtration or electrolysis or reverse osmosis or ion exchange
Electrostatic precipitator or wet electrostatic precipitator or cyclones or fabric/bag filter or ceramic/metal mesh filter or wet scrubber
<b>Conditions and measures related to external treatment of waste (including article waste)</b>
Dispose of waste product or used containers according to local regulations.
<b>Other conditions affecting environmental exposure</b>
No discharge to marine water assumed
Receiving water dilution (fresh or marine) $\geq 10$
Receiving surface water flow $\geq 1.8E4$ m <sup>3</sup> /day
Assumed effluent discharge flow from site $\geq 2E3$ m <sup>3</sup> /day

### 11.2.3. Control of environmental exposure: Use of nickel oxide powder for the production of nickel zinc ferrite cores - Direct discharge to marine water (ERC 5)

<b>Amount used, frequency and duration of use (or from service life)</b>
Daily amount per site $\leq 1.5$ tonnes/day (All the amounts and concentrations are expressed as Ni as this is the driver for the environmental risk assessment.)
Annual amount per site $\leq 337.5$ tonnes/year
Emission days $\geq 225$ days/year
<b>Technical and organisational conditions and measures</b>
Chemical precipitation or sedimentation or filtration or electrolysis or reverse osmosis or ion exchange
Electrostatic precipitator or wet electrostatic precipitator or cyclones or fabric/bag filter or

ceramic/metal mesh filter or wet scrubber
<b>Conditions and measures related to external treatment of waste (including article waste)</b>
Dispose of waste product or used containers according to local regulations.
<b>Other conditions affecting environmental exposure</b>
No discharge to freshwater assumed
Receiving water dilution (fresh or marine) $\geq 100$
Assumed effluent discharge flow from site $\geq 2E3$ m <sup>3</sup> /day

#### 11.2.4. Control of worker exposure: Raw material handling (PROC 26)

<b>Product (article) characteristics</b>
Physical form of product; Solid, medium dustiness
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>
Covers daily exposures up to 8 hours
<b>Technical and organisational conditions and measures</b>
Local exhaust ventilation
Automated task
Semi-closed system
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>
APF of RPE = 10 (90% respiratory protection). For further specification, refer to section 8 of the SDS.
Wear suitable gloves tested to EN374.; For further specification, refer to section 8 of the SDS.

#### 11.2.5. Control of worker exposure: Milling (PROC 2)

<b>Product (article) characteristics</b>
Physical form of product; Solid, low dustiness
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>
Covers daily exposures up to 8 hours
<b>Technical and organisational conditions and measures</b>
Local exhaust ventilation
Ensure automation of the process as far as technically feasible
Semi-closed system

#### 11.2.6. Control of worker exposure: Spray drying (PROC 4)

<b>Product (article) characteristics</b>
Maximum emission potential covered in this ES: Low.
Physical form of product: Damp solid.
<b>Technical and organisational conditions and measures</b>
Local exhaust ventilation
Semi-closed system
Elevated temperature

#### 11.2.7. Control of worker exposure: Calcination (PROC 22)

<b>Product (article) characteristics</b>
--

Maximum emission potential covered in this ES: Low.
Physical form of product: Damp solid.
<b>Technical and organisational conditions and measures</b>
Local exhaust ventilation
Semi-closed system
Elevated temperature

### 11.2.8. Control of worker exposure: Sintering (PROC 22)

<b>Product (article) characteristics</b>
Maximum emission potential covered in this ES: Low (temperature based).
Physical form of product: Solids in various physical forms e.g. powders, pressed powders, pasted powders etc.
<b>Technical and organisational conditions and measures</b>
Ensure automation of the process as far as technically feasible
Closed process with occasional opening
Use of an integrated local exhaust ventilation is required.
Manufacturing and processing of minerals and/or metals at substantially elevated temperature. High temperature processes slightly below melting point / degradation temperature.

### 11.2.9. Control of worker exposure: Handling of nickel zinc solids (PROC 21)

<b>Product (article) characteristics</b>
Maximum emission potential covered in this ES: Low (abrasion based).
Physical form of product; Massive object
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>
Wear suitable gloves tested to EN374.; For further specification, refer to section 8 of the SDS.

### 11.2.10. Control of worker exposure: Wet cleaning (PROC 28)

<b>Product (article) characteristics</b>
Maximum emission potential covered in this ES: Very low.
Physical form of product: Solution and other liquid materials, e.g. suspensions are also covered.
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>
Covers daily exposures up to 8 hours
<b>Technical and organisational conditions and measures</b>
Cleaning machines such as power sweeper, no direct manual cleaning.
Covers use at ambient temperatures.
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>
APF of RPE = 10 (90% respiratory protection).

### 11.2.11. Control of worker exposure: Cleaning/removal of dust (PROC 28)

<b>Product (article) characteristics</b>
Physical form of product: Residual dust.
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>

Covers daily exposures up to 8 hours
<b>Technical and organisational conditions and measures</b>
Cleaning is conducted using cleaning machines, in particular hovering is applied and the use of compressed air is omitted.
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>
APF of RPE = 20 (95% respiratory protection). For further specification, refer to section 8 of the SDS.

### 11.3. Exposure estimation and reference to its source

#### 11.3.1. Environmental release and exposure: Use of nickel oxide powder for the production of nickel zinc ferrite cores - Discharge to fresh water via municipal sewage treatment plant (ERC 5)

Release route	Release rate	Release estimation method
Water	0.075 kg/day	Estimated release factor
Air	0.075 kg/day	Estimated release factor
Soil	0 kg/day	Estimated release factor

Protection target	Exposure estimate	RCR
Fresh water	4.51E-3 mg/L (EUSES 2.1.2)	0.636
Sediment (freshwater)	75.9 mg/kg dw (PEC sediment calculation method for metals)	0.696
Sewage Treatment Plant	0.023 mg/L (EUSES 2.1.2)	0.068
Agricultural soil	16.83 mg/kg dw (EUSES 2.1.2)	0.563

#### 11.3.2. Environmental release and exposure: Use of nickel oxide powder for the production of nickel zinc ferrite cores - Direct discharge to fresh water (ERC 5)

Release route	Release rate	Release estimation method
Water	0.075 kg/day	Estimated release factor
Air	0.075 kg/day	Estimated release factor
Soil	0 kg/day	Estimated release factor

Protection target	Exposure estimate	RCR
Fresh water	5.59E-3 mg/L (EUSES 2.1.2)	0.787
Sediment (freshwater)	104.2 mg/kg dw (PEC sediment calculation method for metals)	0.956
Agricultural soil	16.20 mg/kg dw (EUSES 2.1.2)	0.542

#### 11.3.3. Environmental release and exposure: Use of nickel oxide powder for the production of nickel zinc ferrite cores - Direct discharge to marine water (ERC 5)

Release route	Release rate	Release estimation method
Water	0.075 kg/day	Estimated release factor

Release route	Release rate	Release estimation method
Air	0.075 kg/day	Estimated release factor
Soil	0 kg/day	Estimated release factor

Protection target	Exposure estimate	RCR
Marine water	5.69E-4 mg/L (EUSES 2.1.2)	0.066
Sediment (marine water)	23.2 mg/kg dw (PEC sediment calculation method for metals)	0.213
Agricultural soil	16.20 mg/kg dw (EUSES 2.1.2)	0.542

#### 11.3.4. Worker exposure: Raw material handling (PROC 26)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	0.014 mg/m <sup>3</sup> (Measured data)	0.28
Inhalation, local, long term	0.014 mg/m <sup>3</sup> (Measured data)	0.28
Inhalation, local, acute	0.071 mg/m <sup>3</sup> (Measured data)	< 0.01
Dermal, local, long term	5.18 µg/cm <sup>2</sup> (Measured data)	0.432
Combined, systemic, long term		0.28

#### 11.3.5. Worker exposure: Milling (PROC 2)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	0.012 mg/m <sup>3</sup> (Measured data)	0.24
Inhalation, local, long term	0.012 mg/m <sup>3</sup> (Measured data)	0.24
Inhalation, local, acute	0.035 mg/m <sup>3</sup> (Measured data)	< 0.01
Dermal, local, long term	1 µg/cm <sup>2</sup> (Measured data)	0.083
Combined, systemic, long term		0.24

#### 11.3.6. Worker exposure: Spray drying (PROC 4)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	5E-3 mg/m <sup>3</sup> (Measured data)	0.1
Inhalation, local, long term	5E-3 mg/m <sup>3</sup> (Measured data)	0.1
Inhalation, local, acute	0.016 mg/m <sup>3</sup> (Measured data)	< 0.01
Dermal, local, long term	0.76 µg/cm <sup>2</sup> (Measured data)	0.063
Combined, systemic, long term		0.1

#### 11.3.7. Worker exposure: Calcination (PROC 22)

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	5E-3 mg/m <sup>3</sup> (Measured data)	0.1
Inhalation, local, long term	5E-3 mg/m <sup>3</sup> (Measured data)	0.1
Inhalation, local, acute	0.016 mg/m <sup>3</sup> (Measured data)	< 0.01
Dermal, local, long term	0.76 µg/cm <sup>2</sup> (Measured data)	0.063
Combined, systemic, long term		0.1

**11.3.8. Worker exposure: Sintering (PROC 22)**

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	0.015 mg/m <sup>3</sup> (Measured data)	0.3
Inhalation, local, long term	0.015 mg/m <sup>3</sup> (Measured data)	0.3
Inhalation, local, acute	0.044 mg/m <sup>3</sup> (Measured data)	< 0.01
Dermal, local, long term	0.76 µg/cm <sup>2</sup> (Measured data)	0.063
Combined, systemic, long term		0.3

**11.3.9. Worker exposure: Handling of nickel zinc solids (PROC 21)**

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	9E-3 mg/m <sup>3</sup> (Measured data)	0.18
Inhalation, local, long term	9E-3 mg/m <sup>3</sup> (Measured data)	0.18
Inhalation, local, acute	0.037 mg/m <sup>3</sup> (Measured data)	< 0.01
Dermal, local, long term	5.18 µg/cm <sup>2</sup> (Measured data)	0.432
Combined, systemic, long term		0.18

**11.3.10. Worker exposure: Wet cleaning (PROC 28)**

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	6E-3 mg/m <sup>3</sup> (Measured data)	0.12
Inhalation, local, long term	6E-3 mg/m <sup>3</sup> (Measured data)	0.12
Inhalation, local, acute	0.026 mg/m <sup>3</sup> (Measured data)	< 0.01
Dermal, local, long term	0.76 µg/cm <sup>2</sup> (Measured data)	0.063
Combined, systemic, long term		0.12

**11.3.11. Worker exposure: Cleaning/removal of dust (PROC 28)**

Route of exposure and type of effects	Exposure estimate	RCR
Inhalation, systemic, long term	0.032 mg/m <sup>3</sup> (Measured data)	0.64
Inhalation, local, long term	0.032 mg/m <sup>3</sup> (Measured data)	0.64
Inhalation, local, acute	0.189 mg/m <sup>3</sup> (Measured data)	0.01
Dermal, local, long term	0.76 µg/cm <sup>2</sup> (Measured data)	0.063
Combined, systemic, long term		0.64

**11.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES**

Guidance: Please refer to Section 0.3 of this "ES for Communication".