



Nickel P-Pellets™ (CDN)

Nickel P-Pellets™ are a high purity form of nickel widely used for electroplating with titanium anode baskets. P-Pellets™ are produced by a unique carbonyl gas refining process at the Copper Cliff Nickel Refinery in Sudbury, Canada.

The controlled and consistent purity of P-Pellets™ and the advantages associated with its distinctive shape make this product ideal for general purpose plating with titanium anode baskets:

- Carbonyl refining produces the purest form of nickel available
- Unique shape prevents the formation of bridges and voids in the basket
- Settles uniformly in basket, ensuring uniform current density and high quality deposits
- Flows easily into regular and shaped baskets with standard mesh sizes
- Ideal for use with automated basket loading devices
- Safe to handle (no sharp edges)
- Dissolves at 100% anode efficiency in common nickel plating solutions (containing chlorides)

Dissolution produces a small amount of metallic residue which can be contained using cloth anode bags.

P-Pellets™ are produced in compliance with the following ISO standards: ISO 9001:2008.

For further information about our products, please visit our website (www.vale.com) or contact a regional sales representative.



**10 kg bags, 5 bags per box,
20 boxes per pallet**

Product Description

Form

- Spherical pieces of nickel
- Diameter: approximately 8 - 12 mm

Packing Density

Approximately 5.3 g/cm³ of basket capacity

Packaging

- 10 kg bags, 5 bags per box, 20 boxes per pallet (1,000 kg net weight)
- 1 tonne bulk bags
- 2 tonne bulk bags

Typical Analysis (wt %)

| | |
|-----|-----------|
| Ni* | >99.98 |
| Co | <0.00002 |
| Cu | <0.00004 |
| C | <0.007 |
| Fe | <0.0006 |
| S | <0.0001 |
| Pb | <0.000002 |
| Zn | <0.00002 |

*Nickel determined by difference



1 or 2 tonne bag